


Project Name: \_\_\_\_\_ Contractor Name: \_\_\_\_\_



**50  60  80  FA-CB-XBUR-SRC (Steel) FastSpec™**

Steel Deck – Recover – Fire Rated, Mechanically Attached Cover-Board and Bonded Membrane							
Fire Rating*		Deck Type	Cover-Board (Installed Over Existing Roof)			50, 60, or 80 mil. Single-Ply	Max. Design Pressure**
			Type	Fasteners	Attachment	Attachment	
<input type="checkbox"/>	Unlimited Slope Class 'A'	Min. 22 ga., Type B, Grade 33 Steel	One layer of Gypsum Cover-Board	IB #12 fasteners and 3" steel Insulation plates	Attached (8 per 4 x 8) (16 per 4 x 8)	Vertibond or Waterborne Adhesive applied at the nominal rate of 1 to 1.5 gallons per 100 sq. ft.	-45.0 psf <sup>(1)</sup> (FM-I-90)
<p><i>The above assemblies and the attachments were tested and approved for use in the field of the roof. It is the designer of record and/or the roofing contractor's responsibility to determine the pressures for all three zones of the roof (field, perimeter, and corners per ASCE-7 05 and the building code) and through extrapolation, the lap spacing for the perimeter and corners zones. Contact IB Should you need assistance. The roofing system must be installed in strict accordance with the current 'IB Roof Systems Specifications Manual and Details', the project specifications, the building code, and good roofing practices by an authorized IB Applicator. Deviations from these requirements, not approved in writing by IB Roof Systems and the Authority Having Jurisdiction are not covered by any or implied IB Roof Systems Warranty.</i></p> <p><i>*Existing Roof: SBS or APP Modified, or oxidized Asphalt smooth coated, mineral surfaced, or gravel surfaced fire rated Roofing System.</i></p> <p><b>Approved Cover-Boards:</b> Dens Deck, Dens Deck Prime, Dens Deck DuraGuard, Securock, minimum 1/4" thickness.</p> <p><b>** Minimum pull values on steel deck (per ANSI/SPRI FX 1-05): 550 lbs. (1) Does not constitute an FM system. For reference only.</b></p>							
Solar Reflectance (White)				Initial: 0.87		3-Year Weathered: 0.74	
Thermal Emittance				Initial: 0.88		3-Year Weathered: 0.90	
Available Warranties							
<input type="checkbox"/>	50 Mil Membrane	<input type="checkbox"/> CG	15-Year 'Material Only', Material and Labor, or No Dollar Limit (NDL). Additional warranties also available.				
<input type="checkbox"/>	60 Mil Membrane	<input type="checkbox"/> TR	20-Year 'Material Only', Material and Labor, or No Dollar Limit (NDL). Additional warranties also available.				
<input type="checkbox"/>	80 Mil Membrane	<input type="checkbox"/> CG	25-Year 'Material Only', Material and Labor, or No Dollar Limit (NDL). Additional warranties also available.				
IB Roof Systems are listed with the following agencies:							