

## Sealants

### Caulking



### Product Details

Solar Seal 900 is a superior multi-purpose polymeric-terpolymer sealant. It is a tough exterior grade caulk that bonds to dry, contaminant free surfaces. Solar Seal 900 is completely compatible with all IB Membrane. It is mandatory to use Solar Seal on all factory warranty projects requiring caulking details. Solar Seal 900 is custom colored to perfectly match all of the IB Membranes and is used in conjunction with IB Water Stop on certain details.

- **Coverage:** 15 linear ft. per 10.3 oz. tube.
- **Color:** White, Tan and Gray.
- **Size:** 10.3 oz. tube.
- **Weight:** 10.3 oz. / 12 lbs. per case.
- **Packaging:** Individual tubes / 12 tubes per case.

***Note:** When Solar Seal 900 is stored indoors, out of direct sunlight, and in the original, unopened container the shelf life is 12 months. Always rotate stock.*

Technical Data		
<b>Bond Cohesion</b>	TT-S-230c	No Bond Loss
<b>Shore A Hardness</b>	TT-S-230c	30 Average
<b>Stain Index</b>	TT-S-230c	None
<b>Sag</b>	TT-S-230c	No Sag
<b>UV &amp; Cold Exposure</b>	ASTM-C-920	No Cracking
<b>Elongation</b>	ASTM-D-412	300% - 400%
<b>Tack Free Time</b>	ASTM-C-679	4 Hours
<b>Adhesion-In-Peel</b>	TT-S-1543	30 lbs/in