

Pipe Flashings

Product Description:

IB factory fabricated cone flashings feature a dielectrically welded reinforced IB PVC Single-Ply base and a 60 mil non-reinforced IB PVC Single-Ply upper. IB factory fabricated pipe flashings are designed for easy installation to reduce jobsite labor and callbacks by reducing workmanship errors. Custom sizes and No-Cone pipe flashings are available upon request.

Packaging:

IB factory fabricated cone flashings are shipped in cardboard boxes of assorted sizes.

Use:

IB Pipe Flashings are typically installed around rooftop penetrations such as pipes, conduit, gas lines and other circular profile penetrations and flashings.

Available IB Membrane Colors:

Available in White, Tan, Gray, Brown, Red, Green, Cool Sand, and Cool Stone.



Cone Flashing Specifications				
Flashing Type	Minimum Pipe	Maximum Pipe	Round Base Flashing	Box Quantity
Short A Cone	1/4"	1"	13-1/2"	50
A Cone	1"	2-1/2"	13-1/2"	50
B Cone	2-1/2"	4"	14-1/2"	50
C Cone	4"	8"	17"	25
D Cone	7-1/2"	10"	23"	25
E Cone	10"	14"	28"	25
4" Oval 0.25 Cone	-	-	22"	50
4" Round 0.25 Cone	-	-	21"	50
6" Round 0.25 Cone	-	-	24"	50
8" Round 0.25 Cone	-	-	26"	50